

Product Finish: Chrome

Product code: AT1228
EAN13 barcode: 5060344151696



Note: the image shown may not reflect the product finish, chrome finish is typically depicted.


Product features:

- Metal & acrylic handle construction
- Custom designed for lower to mid pressures
- Traditional French provincial styling
- Quarter turn handle action for precise flow control
- Swivel spout for maximum flexibility

Additional information / Parts included:

Includes 2.5 & 2mm Allen key & triangular stabiliser

Product dimensions:




- Overall Height / projection: 402 mm
- Exit reach: 230 mm
- Exit height: 252 mm
- Centre distance(s):
- Base diameter(s): 50 mm
- Recommended hole diameter: Ø 35 mm
- Max. surface depth: 45 mm
- Spout diameter: 20 mm
- Spout aerator size: 18f

Packaged properties:

Box length: 430mm Box depth: 70mm
Box width: 340mm Units per outer: 5
Tap only weight: 1.81kg Boxed weight: 2.41kg

Product flow characteristics:



- Min / Max water pressure: 0.40 / 5.5 bar
- Recommended / Max water temperature: 46°C / 70°C
- Part G - Mixed flow rate at 3 bar (litres / min): 17.63

- Control valve type: Ceramic disc QT
- Product flow characteristics: Single flow
- Non return valve(s): Integral to hot & cold inlets

- Aerator type: Plastic mesh diffuser
- Accepts revolve / spray areator: No
- Spout connection method: Grub screw

- Tail pipe inlet / outlet size: M10 / 1/2" BSP Male
- Inlet pipe type / length: flexible stainless braided hose / 370 mm

Care instructions summary:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build-up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year