# **PRONT**EAU."

## **PROJECT Monobloc**


Product Finish: Matt Black

Product code: PT1027-2 EAN13 barcode: 5060879990760

#### Product features:

- Stylish 4 way mixer tap delivering domestic hot and cold, ambient and 80-98° filtered water.
- Suppled with 2 x patent pending proximity Hotkey™ activation for 80-98° water, without the Hotkey™ the product reverts to a family safe 3 way mixer.
- 360° rotating thermally insulated spout
- Ceramic disc 1/4 turn smooth action control valves
- Hands free dispensing of 80-98° water possible for heavy pans
- Anti splash aerator as standard


#### Product dimensions:



#### Overall Height / projection: 388 mm

- Exit reach: 222 mm
- Exit height: 278 mm
- Centre distance(s): n/a
- Base diameter(s): 54 mm
- Recommended hole diameter: Ø35 mm
- Max. surface depth: 50 mm
- Spout diameter: 24 mm
- Spout aerator size: M22x1 Male

#### Product flow characteristics:



- Min / Max water pressure: 0.50 / 5.5 bar (mixertap only)
- Recommended / Max incoming domestic hot water temperature: 46°C / 70°C
- Part G Mixed flow rate at 3 bar (litres / min): 13.90
- Control valve type: 1 x Ceramic disc QT hot, 1 x Diverter Cold/Filter
- Product flow characteristics: (C.H&F/Boiling) dual flow
- Aerator type: Neoperl aerator honeycomb dual flow
- Hot and Cold inlet connections: M10 x 1/2" M x 365mm flexi hose
- Non return valve(s): Yes, integral to hot and cold supplies

Care instructions summary:	Warranty Summary (Full details available on request):
<ul> <li>Clean the product regularly as required, using a mild soap and damp cloth, do not use any other cleaners, regular cleaning will prevent the build-up of lime scale and dirt.</li> <li>Residues of sink &amp; worktop cleaners can also cause damage to the mixer tap, so rinse with clean water after using, avoid contact with any abrasives.</li> <li>Proboil4e requires periodic filter change and descaling, see user guide for detail.</li> </ul>	



\*All temperatures quoted are measured within the tank of the boiler and actual spout exit temperature may vary dependant on local conditions.

#### PROBOIL.4E features:

- Controllable tank temperature range from 75°C (holiday/eco mode) to 85,90,95,96, 97, 98°C using the touch screen controls.
- 4 Litre capacity tank, apx. 9 minutes reboil after use
- On screen filter life / replacement indicator
- Intelligent self-diagnostic control
- No external drain connection needed for a simplified and more flexible installation
- Flow limited to 2 litres/min to limit splashing and ensure a smooth flow
- Tool free, hand tight connectors to speed up installation, maintenance and descaling
- Compact size 20.6x25.6x29.1cm (excludes connections)
- 2 Year Warranty\*
- WRAS approval pending

For further information refer to proboil.co.uk and our user guides.

Our premium quality **PRO**BOIL filter offers the following benefits:

- Filtered ambient and 80-98°C drinking water, engineered specifically for hot and ambient water applications
- Included with every **PRO**BOIL system
- 6 month life (based on 19 degrees Clark (London average hardness) and 5 litres per day usage)
- Free filter cartridge recycle scheme
- Superfine 5 micron carbon block filtration
- Chlorine taste and odour reduction.
- pH balanced delivery
- Adjustable hardness settings allows optimised filter life and boiler scale protection in both hard and soft water areas
- Inbuilt corrosion protection
- Mineral adaption and scale reduction for protection
- Simple quarter turn bayonet installation
- Automated on screen life reminder



#### The complete package:

Each **PRONT**EAU system includes:

- A stylish choice of intelligent 4 way **PRONT**EAU mixer taps
- 2 x 4 way mixer tap Hotkeys
- **PRO**BOIL.4E hot water boiler
- PROBOIL advanced scale control filter
- Comprehensive user and installation guide
- Nationwide professional maintenance and service support

### WATER THE WAY YOU WANT IT