

abode


Trydent 1.5 Bowl & drainer





Product dimensions and installation information: note: Symbol indicates position of acoustic pad on stainless products.





Adittional notes:

Overall product size: 1000 x 500 x 175, corner radius 10 mm

Taphole(s) detail: 2 x Ø 35mm, precut Wastehole(s) detail (mm): 90 / 90 / N/A

Min. base unit (mm) (refers to space required for bowl, tap and overflow only): fits 600 carcass
Min. Recessed fitting width (mm): required (bowl(s), tap and overflow: 551
*Worktop cut out size (mm): 976 x 476, corner radius 10, for .DXF cut files please see our webiste
Min. & Max worktop depth or clip depth reach range (mm): 25 - 45
Fitting temple supplied? No, use cut out instructions as supplied
Dishwasher under drainer? Distance from top of worktop to underside of the drainer 10.0 mm

Bowl details: (sizes in mm unless specified otherwise) Bowl 1 (typically main bowl): Bowl 2 (tr

Bowi i (ippically inalii bowi).

Bowl 1 size L x W x D (mm): 400 x 340 x 160 Bowl 1 construction: Pressed, 0.60 mm Bowl 1 floor radius (mm): 45 Bowl 1 Wastehole diameter (mm): 90 Bowl 1 overflow: Slotted, standard pattern Bowl 1 texture: Unbrushed / satin Bowl 1 apx. volume (litres): 15.10

Bowl 2 (typically 1/2 or 3/4 bowl):

Bowl 2 size L x W x D (mm): 300 x 160 x 90 Bowl 2 construction: Pressed, 0.60 mm Bowl 2 floor radius (mm): 20 Bowl 2 Wastehole diameter (mm): 90 Bowl 2 overflow: N/A Bowl 2 texture: Unbrushed / satin Bowl 2 apx. volume (litres): 3.60


Bowl 3:

Bowl 3 size L x W x D (mm): N/A x N/A x N/A Bowl 3 construction: N/A, N/A mm Bowl 3 floor radius (mm): N/A Bowl 3 Wastehole diameter (mm): N/A Bowl 3 overflow: N/A Bowl 3 texture: N/A Bowl 3 apx. volume (litres): N/A



*Important, fabricator / installer notes for undermount & Flushmount sinks:

The cut out size indicated is aligned with outside edge of the bowl top radius (similar to the example below).



You should confirm with your client if the worksurface cutout is to be cut flush, inside or outside this suggested perimeter shape & size.

If you create the cutout smaller or larger than the indicated size then the fit of the accessories may be affected and should be physically checked.

General:

All details are provided in good faith but do not include the tolerances of the material or manufacturing process.

We request that a test cutout is made in scrap timber and checked against the actual sink to be installed before committing to cutting the final worksurface.

Abode can not accept liability for problems or costs incurred by failure to follow this request.

Note: the dimensions on ceramic fireclay products are subject to wider tolerances due to the nature of this natural material and the firing process.

> CAD cutout files can be downloaded from www.abodedesigns.co.uk

