

AKW Part Number : 25498

GW90-2 Low Height Wet Waste with TF Tiled Floor Adaptor



Product Overview

The low depth gravity waste has been designed for ease of installation and flexibility of fitting. The 90mm diameter waste with a 50mm water trap is suitable for Sulby 2, Low Profile and Mullen trays where height restrictions are an issue.

Features

- Shallow 53mm depth
- Suitable for push fit pipe (with included adaptor)
- Suitable for solvent weld pipe (with included adaptor)
- Top access

Benefits

- Very compact design, ideal for solid floor or shallow joists installations
- Allows for easy shower tray installation
- Providing a choice of various installation requirements
- Easy to open for cleaning purposes

Attributes

Contents

1 x GW90-2 Low Height Wet Waste with TF Tiled Floor Adaptor

Testing Standard/Certification

CE and Guaranteed for Life

Patents

Specification

Shallow 53mm depth. Useful for solid floor or shallow joists.
Very compact
Good seals and location
50mm water trap preventing bad odour backflow
Suitable for push fit pipe (with included adaptor)
Suitable for solvent weld pipe (with included adaptor)
Top access for easy cleaning

High flow rate (27 l/min with 15mm head and 1m of pipe)

Guarantees & Approvals



*The lifetime warranty excludes normal wear and tear in general applications, in accordance with AKW installation instructions. It applies only to products being installed for the first time and according to relevant local and national regulations.