Sandringham 21 Water Saving Steel bath 170x70cm 2 Tapholes With Handgrips & Anti-slip* (130 Litres)

ILLUSTRATED

Sandringham 21 water saving bath 170 x 70cm standard gauge steel, with chrome plated grips 2 tapholes, anti-slip* (only 130 Litres)

B9870 Sandringham 21 bath filler 2 hole

S8970 Trap 1½" plastic P with 75mm seal, multi-purpose outlet

suitable for plastic and BS copper pipe

\$8840 1 1/2" Combination bath waste & trap with overflow and

domed clicker

OPTIONS

B9866	Sandringham 21 bath pillar taps		
B9871	Sandringham 21 bath shower 2 hole mixer with shower set		
B9876	Sandringham 21 bath pillar taps, crosshead handles		
B9877	Sandringham 21 bath filler 2 hole, crosshead handles		
B9878	Sandringham 21 bath shower mixer 2 hole with shower set, crosshead handles		
B9882	Sandringham 21 bath pillar taps, lever handles		
B9883	Sandringham 21 bath filler 2 hole, lever handles		
B9884	Sandringham 21 bath shower mixer 2 hole with shower set, lever handles		
S0915	Bath flat front panel		
S0916	Bath flat end panel		
S9365	Bath panel plastic corner edge strip		
S8830	Waste 1½" bath chain and overflow, plastic plug		
A5901	TMV Thermostatic mixing valve 22mm		

ILLUSTRATED PRODUCT DETAILS

Weights		Finishes	
S1839	25.51 KG	S1839	White (01)
B9870	2.10 KG		
S8970	1.00 KG	B9870	Chrome (AA)
S8840	0.31 KG		
Materials		S8970	Neutral / No Finish
S1839	Porcelain Enamelled		(67)
	Steel	S8840	Chrome (AA)
B9870	Chrome Plated Brass		
S8970 S8840	Plastic Plastic	Capacity	
30040	riddic	S1839	130.0 litres (to overflow)
		Flow rates	
		В9870	16.5 Litres per minute @ 3 bar pressure


Standards


Manufactured to BS 1344-3:1998 Standard gauge 2mm porcelain enamelled steel

Special Notes

*Anti-slip reduces the likelihood of slipping but it does not prevent all







ACCREDITATIONS













FEATURES



Sandringham 21 Water Saving Steel bath 170x70cm 2 Tapholes With Handgrips & Anti-slip* (130 Litres)

slipping. Care to be taken when cleaning as aggressive products may reduce the effectiveness of the slip resistant area. Consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device see A5901AA or Part G for guidance.

