# Marlow 21 Oval 48cm Under-countertop Washbasin, Overflow

## **ILLUSTRATED**

S2684	Marlow 21 Oval 48cm under-countertop washbasin with overflow	
A4852	Sensorflow 21 compact washbasin mounted spout with integral sensor, 3.7 litre per minute aerated spray outlet, combined inlet servicing valve and filter, mains	
S8722	Waste 1¼" brass strainer waste, 80mm slotted tail	
S8920	Trap 1¼" plastic resealing bottle, 75mm seal,	

## **OPTIONS**

A4851 Sensorflow 21 compact washbasin mounted spout integral sensor servicing valve and filter, copper tube inlets, battery

A4853 Sensorflow 21 compact washbasin mounted spout with integral sensor, 3.7 litre per minute aerated spray outlet, combined inline servicing valve and filter, link

## **ILLUSTRATED PRODUCT DETAILS**

multi-purpose outlet

Sizes		Finishes		
S2684	w:490 x d:360	S2684	White (01)	
Weights \$2684 A4852 \$8722	7.00 KG 1.60 KG 0.22 KG	A4852 S8722	Chrome (AA)  Chrome (AA)	
S8920 Material S2684	2.00 KG s Fine Fireclay	S8920	Neutral / No Finish (67)	
A4852 S8722 S8920	Chrome Plated Brass Chrome Plated Metal Plastic	Capacity S2684 Flow rate	4.0 litres	
		A4852	3.7 Litres per minute @ 3 bar pressure	
		Designer		
		Robin Levien, RDI		

# Using T645567 fixing clips fixing detail for blockboard countertop T645567 fixing clips sealant No. 10 woodscrew T645567 fixing clips sbolts (set of 4) (not supplied) 15 175

M6.bolts bonded



480 415 360 285 550 480 380 310 620 545 410 335

# **FINISH OPTIONS**



### **Standards**

Washbasin to BS EN 14688 & BS EN 31

## **Special Notes**

This washbasin is not suitable for separate pillar taps. Washbasin mounted on underside of countertop using fixing clips provided. Joint sealed using waterproof sealant (not supplied).

Consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device see A5900AA

