TECHNICAL DATA SHEET



ARTISAN Artisan TMV2 Thermostatic Basin Mixer

Product Specification

Product Code: AR2 THBAS C
Finish: Chrome plated
Product Type: Contemporary

Construction: Bodies are of all brass construction

Valve Type: ½" Standard Valve Cartridge Type: Thermostatic


Supply: Suitable for nominally equal (balanced) inlet

supply pressures only

Inlet Connections: 15mm copper connecting pipes

Working Pressures: Min 0.2 Bar Max 5.0 Bar





Additional Information

- Dual control Flow and temperature are controlled separately giving accurate control of both thermostatic control to bath and shower functions.
- Thermostatic cartridge maintains showering temperature to +/- 1° C by compensating for changes in the incoming water temperature and pressure giving stable outlet temperature.
- •Automatic shut off in the event of hot or cold water supply failure, thus reducing the risk of any injury.
- Factory set to 38°C to eliminate the ability to select unsafe temperature, this can be overridden by the user.
- •Chrome plated to BS EN 248.
- •This product must have nominally equal (balanced) inlet supply pressures to function correctly. If pressures are unequal, then a pressure reducing valve should be used.

Technical Advice: For further information please call 0844 7016273 or email

customercare@bristan.com.

Guarantee: 5 years covering manufacturing faults.

Compliance / Approvals

WRAS: Certificate No: 1407011

Flow Rates (litres per minute)

System Pressure	0.2bar	0.4bar	0.5bar	1.0 bar	2.0 bar	3.0bar	4.0bar	5.0bar
AR2 THBAS C	3.2	6.6	7.9	12.1	17.8	21.8	25.0	28.1







