

ARTISAN LEVER

Thermostatic Lever Handle Bath Shower Mixer



Product Specification

Product Code:	AR2 THLBSM C
Finish:	Chrome plated
Product Type:	Contemporary
Construction:	Bodies are of all brass construction
Valve Type:	Ceramic disc valve
Cartridge Type:	Thermostatic
Supply:	Suitable for nominally equal (balanced) inlet supply pressures only
Inlet Connections:	¾" BSP
Outlet Connections:	G ½"
Working Pressures:	Min 0.2 Bar Max 5.0 Bar



Additional Information

- Dual control – Flow and temperature are controlled separately giving accurate control of both bath and shower functions.
- Product supplied without shower kit.
- Thermostatic cartridge maintains showering temperature to +/- 1°C by compensating for changes in the incoming water temperature and pressure giving stable outlet temperature.
- Automatic shut off in the event of hot or cold water supply failure, thus reducing the risk of any injury.
- Factory set to 38°C to eliminate the ability to select unsafe temperature, this can be overridden by the user.
- Chrome plated to BS EN 248.
- This product must have nominally equal (balanced) inlet supply pressures to function correctly. If pressures are unequal, then a pressure reducing valve should be used.



Flow Rates (litres per minute)

System Pressure	0.2bar	0.5bar	1.0 bar	2.0 bar	3.0bar	4.0bar	5.0bar
Bath Filler	4.4	7.8	11.6	16.8	20.8	24.0	26.9
Through Handset	4.6	8.0	11.7	16.8	21.0	24.2	27.1

Compliance / Approvals

WRAS: Certificate No: 1407010

Technical Advice: For further information please call 0844 7016273 or email customer@bristan.com.

Guarantee: 5 years covering manufacturing faults.

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG
Telephone: 0844 701 6274 Facsimile: 0844 701 6275
Web Site: www.bristan.com Email: enquire@bristan.com



The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.