TECHNICAL DATA SHEET



VERTICO

Thermostatic Exposed Bar Valve with Adjustable Riser

and Integral Diverter to Handset

Product Specification

Product Code: VR SHXMTFF C

Finish: Chrome

Product Type: Contemporary

Construction: Body is of Brass Construction

Compatible Systems: Suitable for all Plumbing Systems

Valve Type: Ceramic Disc Valve
Inlet Connection: 15mm Compression
Working Pressures: Min 0.5 Bar, Max 5.0 Bar

Additional Information

- Chrome plated to BS EN 248
- Dual control Flow and temperature are controlled separately giving accurate control of both
- •Factory set to 38°C with push button override to 46°C.
- Supplied with Wall Mount 11 (WMNT 11 C) fixing kit for easier fast fit installation.
- Shower has internal diverter mechanism.
- Supplied with stylish push button multimode, rub clean handset, adjustable riser and easy clean smooth hose.

Flow Rates (litres per minute)

System Pressure	0.5 Bar	1.0 Bar	2.0 Bar	3.0 Bar	4.0 Bar	5.0 Bar
Open Outlet	8.6	12.9	18.7	23	26.56	29.69
Handset (Mixed)	3.3	5.1	7.3	9.2	10.62	11.88

Compliance / Approvals

Manufactured to comply with WRAS.

Technical Advice: For further information please call 0844 7016273

or email <u>customercare@bristan.com</u>

Guarantee: 5 years covering manufacturing faults.

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG Telephone: 0844 701 6274 Facsimile: 0844 701 6275 Web Site: www.bristan.com Email: enquire@bristan.com







