## AR2 SHXSMFF C

### **ARTISAN Shower Range**

Artisan Thermostatic Surface Mounted

Bar Shower Valve with Adjustable Riser & Fast Fit Connections



#### Features:

- TMV2 thermostatic control for a higher level of performance and protection
- Eco feature on flow control (can be over-ridden)
- Supplied with our wallmount 10 fixing kit for easier retro installation
- Rub clean handset
- Adjustable fixing brackets on

#### **Product Certifications:**



WRAS Certificate No: 1711005 WRAS Expiry Date: 30/11/2022




TMV2 Certificate No: BC1638-1115 TMV2 Expiry Date: 12/11/2020 TMV2 Designation: Low & High **Pressure Showers** 

For more products, visit our website:



| Specification                            |                          |  |  |  |  |
|--|--------------------------|--|--|--|--|
| Style:                                   | Contemporary             |  |  |  |  |
| Finish/Colour:                           | Chrome                   |  |  |  |  |
| Main Construction Material:              | Brass                    |  |  |  |  |
| No of Controls:                          | 2                        |  |  |  |  |
| Shower Type:                             | Bar Shower               |  |  |  |  |
| Shower Head Type:                        | Single Function Handset  |  |  |  |  |
| Valve/Cartridge Type:                    | Exposed                  |  |  |  |  |
| Maximum Hot Water Supply Temperature °C: | 60°C - Pre-set to 38°C   |  |  |  |  |
| Dynamic Pressure Range: (bar)            | 5                        |  |  |  |  |
| Maximum Static Pressure: (bar)           | 10                       |  |  |  |  |
| Plumbing System Suitability:             | All                      |  |  |  |  |
| Working Pressure Range:                  | Min 0.1 Bar, Max 5.0 Bar |  |  |  |  |
| Flow Rate: (I/min @ 3 bar)               | 25.5                     |  |  |  |  |
| Connection Inlet:                        | 15mm compression         |  |  |  |  |
| Connection Outlet:                       | G 1/2" BSP               |  |  |  |  |
| Isolation Valve Included:                | No                       |  |  |  |  |
| Check Valve Included:                    | Yes                      |  |  |  |  |

#### Dimensions (measurements in mm)



| Flow Rates (I/min)             |     |     |      |      |      |      |  |  |
|--------------------------------|-----|-----|------|------|------|------|--|--|
| System Pressure (bar)          | 0.2 | 0.5 | 1    | 2    | 3    | 5    |  |  |
| Through Handset (mixed)        |     | 5.5 | 8.3  | 12   | 14   | 14   |  |  |
| With Flow Regulators Fitted    |     | 10  | 14   | 14   | 14   | 14   |  |  |
| Without Flow Regulators Fitted | 5   | 9.4 | 14.2 | 20.8 | 25.5 | 33.2 |  |  |

# TECHNICAL DATA



