COBALT SHWR PK

COBALT Shower Range Complete Cobalt Recessed Dual Control Shower Pack



Features:

- This shower pack has soft square handles on our Colbalt shower valve with integral two outlet diverter. It has a 200mm square fixed head with shower arm; and an adjustable riser shower kit with a single function handset.
- The shower valve has been designed to fit in any UK wall cavity and therefore only needs a 35mm deep cavity space
- Dual control flow and temperature are controlled separately
- Cartridge can be accessed from the front, Requires rear access to service filters
- Wall outlet designed with Bristan's Wall Mounted Technology for easier installation

Product Certifications:





| Chrome Plated |
|-----------------------------------|
| D 100 |
| Brass; ABS |
| 2 |
| Recessed Dual Control |
| Both |
| Adjustable riser with Fixed Head |
| 35mm Thermostatic Cartridge |
| 65 |
| Suitable for all plumbing systems |
| 0.2 |
| 5.0 |
| 10 |
| 15mm Compression |
| G 1/2" |
| No |
| Yes |
| |

100 55 200 650 Ø22 45 80 150 115 Centres 80 68 50 330 200 ■ GI/2" (male) GI/2" (male) GI/2" (female) 200 54

Flow Rates (I/min)

2.2

6.1

6.7

0.5

12.8

12.5

| | | | | |
|-------|------|------|---------|--|
| | | | | |
| | | | | |
| +++++ | | | | |
| | | | لكلكدكك | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

1

19

18.5

2

27.6

27

3

33.8

33

5

43.6

42.6

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com. * - Non-chrome product finishes carry a 3 year guarantee on finish. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.

System Pressure (bar)

Outlet 1

Outlet 2

Dimensions (measurements in mm)