ARTISAN SHWR PK2



Features:

- This simplistic shower pack contains an Artisan shower valve with an integral two outlet diverter. It has a 200mm round fixed head with shower arm; and an adjustable riser shower kit with a large multi function rub-clean handset.
- The shower valve has been designed to fit in any UK wall cavity and therefore only needs a 35mm deep cavity space
- Dual control flow and temperature are controlled separately
- Fully serviceable from the front
- Wall outlet designed with Bristan's Wall Mount Technology for easier installation

Product Certifications:



For more products, visit our website: <u>http://www.bristan.com</u>

	Flow Rates (I/min)						
1923 12 C	System Pressure (bar)	0.2	0.5	1	2	3	5
	Fixed Head	2.2	3.5	5.0	7.0	8.6	11.1
E1726421	Through Handset	2.1	3.3	4.7	6.6	8.1	10.5

TECHNICAL DATA SHEET





Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com. The information contained on this page was correct at date of issue. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.

Specification					
Finish/Colour:	Chrome Plated				
Main Construction Material:	Brass; ABS				
No of Controls:	2				
Shower Type:	Dual Control				
Shower Head Type:	Fixed Head				
Valve/Cartridge Type:	3/4" Ceramic Disc Valve 1/4 turn				
Maximum Hot Water Supply Temperature ^o C:	65				
Maximum Static Pressure: (bar)	10				
Plumbing System Suitability:	Suitable for all plumbing systems				
Minimum Dynamic Pressure:	0.2 bar				
Maximum Dynamic Pressure:	5.0 bar				
Connection Inlet:	15mm Compression				
Connection Outlet:	G 1/2"				
Isolation Valve Included:	No				
Check Valve Included:	Yes				

