# FRZ BF C

### FRENZY Tap Range Frenzy Bath Filler Chrome



Specification				
Product Type:	Bathroom Tap			
Main Construction Material:	Brass			
Mount Type:	Deck Mounted			
Handle Type:	Lever Handle			
Connection Inlet:	3/4" BSP			
Connection Outlet:	M28 Flow Straightener			
Number of Tap Holes:	2			
Valve/Cartridge Type:	3/4" Ceramic Disc Valve			
Plumbing System Requirements:	Suitable for all plumbing systems			
Minimum Dynamic Pressure (bar):	0.2 bar			
Maximum Dynamic Pressure (bar):	5.0 bar			
Maximum Hot Water Temperature °C:	65°C			
Maximum Static Pressure (bar):	10 bar			
Flow Type:	Single Flow			
Isolation Included:	No			

Dimensions (measurements in mm)


#### Features:

- Long life and easy to use 1/4 turn ceramic disc valves
- Metal back nuts for added durability
- Easy-to-use lever handles
- Chrome plated to BS EN 248

### **Product Certifications:**



WRAS Certificate No: 2004910 WRAS Expiry Date: 30/04/2025



For more products, visit our website: http://www.bristan.com



Flow Rates (I/min)							
System Pressure (bar)	0.2	0.5	1	2	3	5	
FRZ BF C (mixed)	29.5	48.6	68.3	97.6	119.5	154.2	

## TECHNICAL DATA SHEET



BRISTAN