## **GWF BASNW C**

## GLIDE Tap Range Glide Waterfall Basin Mixer without Waste Chrome



		res:
_	$\sim$	raci
	-c	H E S

- Long life ceramic cartridge for added durability and ease of use
- Metal fixing nut for added durability
- Flexible tails included

Specification						
Product Type:	Bathroom Taps					
Main Construction Material:	Brass					
Mount Type:	Deck Mounted					
Handle Type:	Lever Handle					
Connection Inlet:	1/2" BSP Flexible Tails					
Connection Outlet:	Stainless Steel Integral Aerator					
Number of Tap Holes:	1					
Valve/Cartridge Type:	35mm Single Lever Cartridge					
Plumbing System Requirements:	Suitable for all plumbing systems					
Minimum Dynamic Pressure (bar):	0.1 bar					
Maximum Dynamic Pressure (bar):	5.0 bar					
Maximum Hot Water Temperature °C:	65°C					
Maximum Static Pressure (bar):	10 bar					
Flow Type:	Single Flow					
Isolation Included:	No					

Dimensions (measurements in mm)





WRAS Cert. Number: 1911909 WRAS Expiry Date: 30/11/2024





For more products, visit our website: http://www.bristan.com



<del>48</del> →	94
30	
134	T
	73
53	133

Flow Rates (I/min)										
System Pressure (bar)	0.1	0.5	1	2	3	5				
GWF BASNW C (mixed)	4.2	9.4	13.3	18.8	23	29.7				

## TECHNICAL DATA SHEET



