SOH BSM C

SOHO Tap Range Soho Bath Shower Mixer Chrome



_			
ь.	\sim	+111	res:
	Ca	uu	II CO.

- Long life and easy to use 1/4 turn ceramic disc valves
- Metal back nuts for added durability
- Includes 1.5m hose, rub-clean anti-limescale handset and wall bracket

Specification					
Product Type:	Bathroom Taps				
Main Construction Material:	Brass				
Mount Type:	Deck				
Handle Type:	Square				
Connection Inlet:	3/4" BSP				
Connection Outlet:	G 1/2"				
Number of Tap Holes:	2				
Valve/Cartridge Type:	3/4" Ceramic Disc Valve - 1/4 turn				
Plumbing System Requirements:	Suitable for all plumbing systems				
Minimum Dynamic Pressure (bar):	0.3 bar				
Maximum Dynamic Pressure (bar):	5 bar				
Maximum Hot Water Temperature °C:	65°C				
Maximum Static Pressure (bar):	10 bar				
Flow Type:	Single				
Isolation Included:	No				

Product Certifications:



WRAS Certificate No: 1909056 WRAS Expiry Date: 30/09/2024







For more products, visit our website: http://www.bristan.com



Dimensions (measurements in mm)





Flow Rates (I/min)								
System Pressure (bar)	0.3	0.5	1	2	3	5		
Through Bath Filler (mixed)	6.9	8.9	12.6	17.8	21.8	28.1		
Through Handset (mixed)	5.5	7.1	10	14.1	17.3	22.3		

TECHNICAL DATA SHEET



