PRISM Tap Range Prism Eco Basin Mixer with Pop-up Waste

D12

Specification

Taps

Brass

1

Deck Mounted

Lever Handles

M10 x 15mm Flexi Tails

3.5l/min Flow Limiting M24 Aerator

40mm Ceramic Disc Cartridge

PM EBAS C

Product Type:

Mount Type: Handle Type:

Connection Inlet:

Connection Outlet:

Number of Tap Holes:

Valve/Cartridge Type:

Main Construction Material:



Featu

SW

WRAS C WRAS E

For more http://w

Ş

- Lonc adde
- Meta dura
- Supp minu redu incre
- Chro
- Easy

Produ

| | | J J |
|---|--|-----------------------------------|
| | Plumbing System Requirements: | Suitable for all plumbing systems |
| | Minimum Dynamic Pressure (bar): | 0.5 bar |
| ires: | Maximum Dynamic Pressure (bar): | 5.0 bar |
| g life ceramic cartridge for ed durability and ease of | Maximum Hot Water Temperature °C: | 65°C |
| | Maximum Static Pressure (bar): | 10 bar |
| al fixing nut for added | Flow Type: | Single Flow |
| ability pplied with 3.5 litre per | Isolation Included: | No |
| ute flow limiting aerator to uce water consumption and ease water efficiency ome plated to BS EN 248 y to use lever handles | Dimensions (measurements in mm) | |
| uct Certifications: | 104 | 50 |
| | 100 32 | |
| RAS | | |
| DPRODUCT | | |
| Certificate No: 1611005 Expiry Date: 30/11/2021 | | |
| r Label 3.5 l/min re products, visit our website: rww.bristan.com | | 63 GI 1/4" |
| | 157 | |
| | | |
| 条班 | Flow Rates (I/min) | |
| | System Pressure (bar) | 0.5 1 2 3 5 |
| | PM EBAS C (mixed) | 3.5 3.5 3.5 3.5 3.5 |
| ECHNICAL ATA | P QUALITZ S 10 YEARS R P YEARS R P 10 YEARS R P YEARS R P 10 YEARS R | BRISTAN |

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com.

RANT

* - 10 year guarantee applies to products purchased on or after 01/04/2021. Non-chrome product finishes carry a 3 year guarantee on finish. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.