## PM2 CSHCVO C

## **PRISM Shower Range**

Prism Concealed Concentric Shower
Valve Only Chrome



Specification					
Finish/Colour:	Chrome				
Main Construction Material:	Brass				
No of Controls:	2				
Shower Type:	Concentric				
Valve/Cartridge Type:	Thermostatic				
Maximum Hot Water Supply Temperature °C:	65				
Plumbing System Suitability:	Suitable for all plumbing systems				
Minimum Dynamic Pressure (bar):	0.2				
Maximum Dynamic Pressure (bar):	5.0				
Maximum Static Pressure (bar):	10				
Connection Inlet:	15mm Compression				
Connection Outlet:	G 1/2"				
Isolation Valve Included:	No				
Check Valve Included:	Yes				

## Features:

- 15mm inlet connections
- Thermostatic cartridge with preset temperature stop at 42°C
- Supplied with 2 x 8L/min flow regulators
- Easy installation with an adjustable faceplate that fits total wall depths from 48.5mm to 72mm for a perfect flush finish
- Supplied with Easyfit wall outlet

## **Product Certifications:**



WRAS Certificate No: 2206907 WRAS Expiry Date: 30/06/2027





For more products, visit our website: <a href="http://www.bristan.com">http://www.bristan.com</a>



Dimensions (measurements in mm)						
40.5	220					
48.5						
140						
<del> </del>	Centres					
	168					
59 54	-					

Flow Rates (I/min)									
System Pressure (bar)	0.2	0.5	1	2	3	5			
With Flow Limiters (mixed)	3.4	5.4	7.8	11.3	11.1	11.4			
Without Flow Limiters (mixed)	9	15.5	22.5	31.8	39.0	50.3			

TECHNICAL DATA SHEET



performance of its products and so reserves the right to change specifications without prior notice.

**BRISTAN**