SAFFRON BB SHWR PK

SAFFRON Shower Range

Saffron Brushed Brass Concealed
Dual Control Shower Pack



Features:

- All in one box pack includes shower valve with integral two outlet diverter, slimline 200mm round fixed head with shower arm, and shower kit with an adjustable riser rail plus a multi function handset and wall outlet.
- Rub clean handset and fixed head - limescale and debris build-up is quickly and easily removed by rubbing a finger or a cloth over the nozzles.
- On-trend brushed brass finish to make a statement in your bathroom.
- Easy installation with an adjustable faceplate that fits total wall depths from 60mm to 75mm for a perfect flush finish
- Dual control Flow and temperature are operated separately giving accurate control of both.
- Cartridge can be accessed from the front for easy servicing.
- 15mm inlet connections.
- 5-year parts and 1 year labour guarantee for peace of mind.
- Also available in chrome and black.
- Co-ordinating range of Bathroom taps available.


Product Certifications:	Proc	luct	Certifi	cations:
--------------------------------	------	------	---------	----------





Specification						
Finish/Colour:	Brushed Brass					
Main Construction Material:	Brass; ABS					
No of Controls:	2					
Shower Type:	Dual Control					
Shower Head Type:	Fixed Head and Adjustable Riser Kit					
Valve/Cartridge Type:	Thermostatic Cartridge & 40mm Single Lever Cartridge					
Maximum Hot Water Supply Temperature °C:	65					
Plumbing System Suitability:	Suitable for all plumbing systems					
Minimum Dynamic Pressure (bar):	0.2					
Maximum Dynamic Pressure (bar):	5					
Maximum Static Pressure (bar):	10					
Connection Inlet:	15mm Compression					
Connection Outlet:	G 1/2"					
Isolation Valve Included:	No					
Check Valve Included:	Yes					

Dimensions (measurements in mm)



Flow Rates (I/min)									
System Pressure (bar)		0.5	1	2	3	5			
Through Handset (mixed)		5	7.3	7.8	8.9	9.8			
Through Fixed Head (mixed)		5.9	6.5	8.1	8.5	9.6			
Through Handset (without flow regulators)		5.8	8.7	12.9	16	21			
Through Fixed Head (without flow regulators)		9.3	13.5	19.5	23.3	24.8			





BRISTAN