ORTA Tap Range Orta Basin Taps Chrome



Specification					
Product Type:	Bathroom Taps				
Main Construction Material:	Brass				
Mount Type:	Deck				
Handle Type:	Paddle				
Connection Inlet:	1/2" BSP				
Connection Outlet:	M16 Aerator				
Number of Tap Holes:	2				
Valve/Cartridge Type:	1/2" Ceramic Disc Valve - 1/4 turn				
Plumbing System Requirements:	Suitable for all plumbing systems				
Minimum Dynamic Pressure (bar):	0.2 bar				
Maximum Dynamic Pressure (bar):	5 bar				
Maximum Hot Water Temperature °C:	65°C				
Maximum Static Pressure (bar):	10 bar				
Isolation Included:	No				

Dimensions (measurements in mm)

Features:

- Long life 1/4 turn ceramic disc valves for added durability and smooth control.
- Robust metal fixing nut to secure the tap in place reducing the risk of loosening over time.
- A hard-wearing, flawless, scratch resistant chrome finish that lasts for years. Salt spray tested to ensure added durability.
- Supplied with pre-fitted flow limiters to reduce water flow to 4l/min per spout
- 10 year parts and 1 year labour guarantee for peace of mind.

Product Certifications:

Water Label

♦3.9 I/min

For more products, visit our website:



7 1 28		
	<u> </u>	
	116	

Flow Rates (I/min)									
System Pressure (bar)	0.2	0.5	1	2	3	5			
OR 1/2 C (Cold)	2.8	4	3.8	3.8	3.9	3.8			
OR 1/2 C (Hot)	2.8	4	3.8	3.8	3.9	3.8			

TECHNICAL DATA SHEET





Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com.
* - 10 year guarantee applies to products purchased on or after 01/04/2021. See www.bristan.com/guarantees for more information. The information contained on this page was correct at