

PM2 SQSHXAR C

PRISM Shower Range Prism Exposed Sequential Chrome Shower Valver with Adjustable Riser Kit



Features:

- The versatile Prism Thermostatic Exposed Single-Control Shower Valve in chrome delivers contemporary design with sequential temperature control for modern bathrooms. A family-safe 42°C preset and a rub-clean handset ensure reliable performance and easy maintenance.
- Save time and avoid plumbing changes with a shower that fits your existing pipework, thanks to adjustable inlets for centres between 136mm and 158mm.
- Save water without compromising performance thanks to two built-in 8L flow regulators
- Comes complete with riser rail with adjustable fixing bracket, rub-clean anti-limescale handset and hose
- Built to last, backed by a lifetime parts and 1-year labour guarantee

Product Certifications:




WRAS Certificate No: 2205903
WRAS Expiry Date: 31/05/2027



Specification

Finish/Colour:	Chrome
Main Construction Material:	Brass
No of Controls:	1
Shower Type:	Bar Shower
Shower Head Type:	Handset
Shower Kit:	Adjustable Riser
Valve/Cartridge Type:	Thermostatic Sequential Cartridge
Maximum Hot Water Supply Temperature °C:	65
Plumbing System Suitability:	Suitable for all plumbing systems
Minimum Dynamic Pressure (bar):	0.1
Maximum Dynamic Pressure (bar):	5.0
Maximum Static Pressure (bar):	10
Connection Inlet:	15mm Compression
Connection Outlet:	G 1/2"
Isolation Valve Included:	No
Check Valve Included:	Yes

Dimensions (measurements in mm)



Flow Rates (l/min)

System Pressure (bar)	0.1	0.5	1	2	3	5
Through Handset (mixed)	2.4	5.5	7.7	10.9	13.4	17.3

TECHNICAL
DATA
SHEET



BRISTAN

D5

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com.

* - Lifetime guarantee applies to products purchased on or after 01/04/2026. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Listed flow rates are indicative for the product. Different plumbing systems and flow regulators can produce higher or lower results. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.