

PM2 SQSHXDIV C

PRISM Shower Range Prism Exposed Sequential Chrome Shower Valver with Diverter and Rigid Riser Kit



Features:

- The versatile Prism Thermostatic Exposed Single-Control Shower Valve in chrome delivers reliable temperature control with contemporary appeal. It features a 42°C safety stop and 8L flow regulators to naturally reduce water consumption while maintaining consistent performance.
- Comes complete with diverter, shower rose, rigid riser, rub-clean anti-limescale handset and hose
- Save time and avoid plumbing changes with a shower that fits your existing pipework, thanks to adjustable inlets for centres between 136mm and 158mm.
- Save water without compromising performance thanks to two built-in 8L flow regulators
- Built to last, backed by a lifetime parts and 1-year labour guarantee

Product Certifications:




WRAS Certificate No: 2207908
WRAS Expiry Date: 31/07/2027



Specification

Finish/Colour:	Chrome Plated
Main Construction Material:	Brass
No of Controls:	1
Shower Type:	Exposed Sequential Cartridge
Shower Head Type:	Fixed Head and Handset
Shower Kit:	Rigid Riser
Valve/Cartridge Type:	Thermostatic Sequential Cartridge
Maximum Hot Water Supply Temperature °C:	65
Plumbing System Suitability:	Suitable for high pressure systems only
Minimum Dynamic Pressure (bar):	1
Maximum Dynamic Pressure (bar):	5
Maximum Static Pressure (bar):	10
Connection Inlet:	15mm Compression
Connection Outlet:	G 1/2"
Isolation Valve Included:	No
Check Valve Included:	Yes

Dimensions (measurements in mm)



Flow Rates (l/min)

System Pressure (bar)	1	2	3	4	5
Through Fixed Head (with flow limiters)	6.4	9.4	11.6	13.4	14.5
Through Handset (with flow limiters)	5.2	7.7	9.6	11.1	12.6
Through Fixed Head (without flow limiters)	6.6	9.5	11.9	13.7	15.5
Through Handset (without flow limiters)	5.3	7.8	9.8	11.3	13.1

TECHNICAL
DATA
SHEET



BRISTAN

D7

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com.

* - Lifetime guarantee applies to products purchased on or after 01/04/2026. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Listed flow rates are indicative for the product. Different plumbing systems and flow regulators can produce higher or lower results. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.