

QB SHXDIVCTFF BLK

QUBO Shower Range Qubo Safe Touch Thermostatic Rigid Riser Diverter Bar Shower Black



Features:

- Fast, hassle-free installation with built-in front facing isolation valves that make it easy to fit, maintain and replace.
- Shower safely with automatic shut-off protection if hot or cold water supply fails
- Stay protected with Safe Touch technology that keeps the valve cool to the touch
- Built to last, backed by a lifetime parts and 1-year labour guarantee


Product Certifications:



WRAS Certificate No: 240903006
WRAS Expiry Date: 30/09/2029




For more products, visit our website:
<http://www.bristan.com>



Specification

Finish/Colour:	Black
Main Construction Material:	Brass; ABS; Stainless Steel
No of Controls:	2
Shower Type:	Bar Shower
Shower Head Type:	Both
Shower Kit:	Adjustable riser with Fixed Head
Valve/Cartridge Type:	Thermostatic Cartridge
Maximum Hot Water Supply Temperature °C:	60
Plumbing System Suitability:	Suitable for high pressure systems
Minimum Dynamic Pressure (bar):	1
Maximum Dynamic Pressure (bar):	5
Maximum Static Pressure (bar):	10
Connection Inlet:	15mm Compression
Connection Outlet:	G1/2"
Isolation Valve Included:	Yes
Check Valve Included:	Yes

Dimensions (measurements in mm)



Flow Rates (l/min)

System Pressure (bar)	1	2	3	5
Through Handset (mixed)	4.3	6.3	7.6	8.3
Through Fixed Head (mixed)	6.1	8.6	9.8	9.4

TECHNICAL
DATA
SHEET



BRISTAN

D3

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com.

* - Lifetime guarantee applies to products purchased on or after 01/04/2026. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Listed flow rates are indicative for the product. Different plumbing systems and flow regulators can produce higher or lower results. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.