

NZA SHXAR C

ONZA Shower Range

Onza Thermostatic Exposed Shower Valve with Riser Kit Chrome



Features:

- The Onza Mini Valve Shower in polished chrome brings subtle elegance and smooth lines to any bathroom style. Thermostatic control with a 42°C safety stop and automatic shut-off protection ensures secure, reliable performance.
- Supplied with everything you need, including shower valve, hose, hose retainer, riser rail and a rub-clean anti-limescale single function handset
- Shower safely with automatic shut-off protection if hot or cold water supply fails
- Effortless fitting with adjustable brackets that reuse existing screw holes
- Built to last, backed by a lifetime parts and 1-year labour guarantee

Product Certifications:



WRAS Certificate No: 240403011
WRAS Expiry Date: 30/04/2029


TMV2 Certificate No: 2503305
TMV2 Designation: HP-SE
TMV2 Expiry Date: 16/03/2030



Specification

Finish/Colour:	Chrome Plated
Main Construction Material:	Brass; ABS; Stainless Steel
No of Controls:	1
Shower Type:	Sequential Mini Valve
Shower Head Type:	Adjustable
Shower Kit:	Adjustable Riser
Valve/Cartridge Type:	Sequential Cartridge
Maximum Hot Water Supply Temperature °C:	60
Plumbing System Suitability:	Suitable for all plumbing systems, ideally balanced
Minimum Dynamic Pressure (bar):	0.2**
Maximum Dynamic Pressure (bar):	5**
**TMV2 Rated only between 1 bar minimum and 5 Bar Maximum Dynamic Pressure	
Maximum Static Pressure (bar):	10
Connection Inlet:	15mm Compression
Connection Outlet:	G 1/2"
Isolation Valve Included:	No
Check Valve Included:	Yes

Dimensions (measurements in mm)



Flow Rates (l/min)

System Pressure (bar)	0.2	0.5	1	2	3	5
Through Handset (mixed)	1.7	5.4	7.6	8.3	8.8	8.8

TECHNICAL DATA SHEET



BRISTAN

D5

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com.

* - Lifetime guarantee applies to products purchased on or after 01/04/2026. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Listed flow rates are indicative for the product. Different plumbing systems and flow regulators can produce higher or lower results. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.