

TRD RISE C

SHOWER ACC Shower Range Traditional Rigid Riser Shower Kit Chrome



Features:

- Start using it straight away with the shower rose included
- Enjoy lasting brilliance with our flawless, scratch-resistant chrome finish that's salt spray tested for durability
- Built to last, backed by a lifetime parts and 1-year labour guarantee

Product Certifications:




For more products, visit our website:
<http://www.bristan.com>



Specification

Finish/Colour:	Chrome Plated
Main Construction Material:	Brass
Shower Kit:	Rigid Riser
Shower Head Type:	Fixed Head
Rub Clean Handset:	N/A
Mounting Type:	Wall
Plumbing System Suitability:	Suitable for all plumbing systems
Minimum Dynamic Pressure (bar):	0.2 bar
Maximum Dynamic Pressure (bar):	5 bar
Maximum Static Pressure (bar):	10 bar
Maximum Hot Water Supply Temperature °C:	65
Connection Inlet:	15mm Compression
Connection Outlet:	N/A
Isolation Included:	No
Check Valve Included:	No
What's Included:	1 x Riser Rail, 1 x Gauze Seal, 1 x Shower Rose, 1 x Riser Arm, 1 x Riser Bracket, 3 x Nuts And Olives, 1 x Adaptor, 1 x Allen Key, 2 x Screws, 2 x Rawl Plugs, 1 x Fitting Instructions

Dimensions (measurements in mm)



Flow Rates (l/min)

System Pressure (bar)	0.2	0.5	1	2	3	5
Through Fixed Head (mixed)	3.4	5.4	7.7	10.9	13.3	17.2

TECHNICAL
DATA
SHEET



BRISTAN

D4

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com.

* - Lifetime guarantee applies to products purchased on or after 01/04/2026. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Listed flow rates are indicative for the product. Different plumbing systems and flow regulators can produce higher or lower results. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.