

N2 CSHCVO C

1901 Shower Range 1901 Concealed Concentric Chrome Shower Valve Only



Features:

- The 1901 Concealed Thermostatic Dual Control Shower Valve in chrome combines Edwardian styling with modern reliability. A thermostatic cartridge maintains consistent temperature with a safety stop at 42°C, while integrated flow regulators naturally reduce water consumption.
- Enjoy peace of mind with a 42°C safety stop, including override when required
- Easy installation with an adjustable faceplate that fits total wall depths from 48.5mm to 72mm for a perfect flush finish
- Save water without compromising performance thanks to two built-in 8L flow regulators
- Built to last, backed by a lifetime parts and 1-year labour guarantee

Product Certifications:




WRAS Certificate No: 2206907
WRAS Expiry Date: 30/06/2027

Specification

Finish/Colour:	Chrome Plated
Main Construction Material:	Brass
No of Controls:	2
Shower Type:	Concealed Concentric
Valve/Cartridge Type:	Concentric Thermostatic
Maximum Hot Water Supply Temperature °C:	65
Plumbing System Suitability:	Suitable for plumbing systems - Ideally balanced
Minimum Dynamic Pressure (bar):	0.2
Maximum Dynamic Pressure (bar):	5
Maximum Static Pressure (bar):	10
Connection Inlet:	15mm Compression
Connection Outlet:	G1/2"
Isolation Valve Included:	No
Check Valve Included:	Yes

Dimensions (measurements in mm)



Flow Rates (l/min)

System Pressure (bar)	0.2	0.5	1	2	3	5
Valve Only (mixed)	9.0	5.4	7.8	11.3	11.1	11.4

TECHNICAL
DATA
SHEET



BRISTAN

D8

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG. Web Site: www.bristan.com Telephone: 0330 026 6273. Email: enquire@bristan.com.

* - Lifetime guarantee applies to products purchased on or after 01/04/2026. See www.bristan.com/guarantees for more information. The information contained on this page was correct at date of issue. Listed flow rates are indicative for the product. Different plumbing systems and flow regulators can produce higher or lower results. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuous improvement in design and performance of its products and so reserves the right to change specifications without prior notice.