

AFTERCARE INSTRUCTIONS

Your fitting has a high quality finish and should be treated with care to preserve the visible surfaces.

All surface finishes will wear if not cleaned correctly, the only safe way to clean your mixer is to wipe with a soft damp cloth. Stains can be removed using washing up liquid. All bath cleaning powders and liquids will damage the surface of your fitting, even the non-scratch cleaners.

GUARANTEE

All products are manufactured to the highest standards and a 5 year guarantee covers any defect in manufacture.

As gold and special effect finishes are softer than chromium plate, special care must be taken when cleaning, a 3 year guarantee covers these finishes.

NOTE: The 5-year guarantee on the cartridge is invalidated if damaged by any waterborne debris.

In the interests of continuous product development we reserve the right to alter specification as necessary

PRODUCT CODE: SY ON ½ C CD & SY SL ½ C CD

PRODUCT IDENTIFICATION CODE LASER ETCHED ON PRODUCT

Installer please fill in code here _____.

TELEPHONE HELPLINE! +44 (0)844 701 6273

Bristan Group Limited
Birch Coppice Business Park
Dordon
Tamworth
Staffordshire
B78 1SG
UK
A Masco Company
Website: www.bristan.com
Telephone: +44 (0) 844 701 6274
Facsimile: +44 (0) 844 701 6275
Email: enquire@bristan.com

BRISTAN

Spray Basin Tap

Fitting Instructions & Contents List



This product has been approved by the Bathroom Manufacturers Association (BMA) under its labelling Water Efficient Product Labelling Scheme. By installing this product, you will be able to reduce the amount of water you use in your home and the amount of energy you use to heat it; a boost for the environment and your pocket.

Please keep these instructions for future reference and request of replacement part

WATER PRESSURE

These taps are suitable for use at all supply pressures. If the taps are installed at low pressure (tank fed) then the minimum height from the outlet of the nozzle to the underside of the cold tank should be at least 2 metres to ensure adequate performance.

These taps should be installed in compliance with Water Regulations. For further details contact your Local Water Authority.

INSTALLATION

1. Identify all components and check for completeness, particularly before arranging fitting.
2. Install the taps into the basin, using the washers (6) and backnuts (7) provided.
3. Connect the hot and cold water supplies.
4. Un-screw the spray guides (8,9 &10) from the taps.
5. Turn on the water supplies. Open both taps letting the water flow for a few minutes to flush the system.
6. Refit the spray guides (8,9 &10) to the taps.
7. Check all joints and connections for leaks.
8. See over the page for aftercare instructions.

MAINTENANCE

If the fitting begins to drip

1. Turn off the water supply.
2. Prise off the head cap (1), unscrew the head retaining screw (2).
3. Remove fitting head (4) and unscrew the valve (5) from the body.
4. Carefully clean seating and rubber washer and check the ceramic discs for damage.
5. Replace valve and turn on the water supply.
6. Contact our helpline if problem persists.

