Burlington®

Simply Exclusive Classically styled bathrooms



High-level pan with high-level white aluminium cistern and high-level flush pipe kit

Code

T59 WHI White aluminium high level cistern including cistern fittings

High level flush pipe kit including lever, rigid pull chain, flush T30 CHR

pipes, reverse screw cistern connector, stopper and ornate

P2 Low/high level pan

Barcodes: T30 CHR (5055806007024),P2 (5055806005198),T59 WHI

(5055806007529) **Technical Specification** Size: 430 x 670 x 2400 mm

Finishes: P2 White; T59 WHI White; T30 Chrome plated

Product Type: Traditional

Material: P2 Vitreous china; T30 Bodies are of all brass construction; T59 WHI

LM25 Aluminium Weight: 31.1 kg

Overall Height: max 240cm, min 232cm

Additional information

The high level level wc uses a standard low level pan (P2) and specialed high level cistern, connected with a medium level flush pipe kit T30 CHR

The flush mechanism comes in two options : dual flush rod pull cistern C5, or single flush chain pull cistern C28PK

A special flush pipe kit that allows the cistern to be placed on a wall next to the pan is available : Angled Flush Pipe Kit T34 CHR

Low Level wc can be used where the soil pipe is located in the floor. The pan can be located over the soil pipe by cutting the horizontal flush pipe to length.

The cistern height can be varied by cutting the vertical flush pipe to length maximum height is 2,380mm to the top of the cistern, minimum height is 1,625mm. Water Inlet valve hole is located on the base of cistern tank on the right hand side Bottom inlet valve (SP5A). Back inlet valve available as optional item (SP511).

P trap standard height pan - height from floor to pan rim is 40cm.

Regal Height pan (floor to pan rim height 48cm) available : P16 Ceramic soil connection pipes : straight connector to the wall : C29. The S trap connector bending down to the floor : C26

Cistern can be used with optional decorative Ornate Brackets T32 CHR High level wc can be used with standard Burlington toilet seats or with the Throne seats (S14 & S15)

Supplied with floor fixings.

Recommended to be used with cistern tank isolation valve W25

Compliance/Approvals:

BS EN 997:2012

WC pans and WC suites with integral trap Chrome plated to BS EN248:2002

Sanitary tapware. General specification for electro deposited coatings of Ni-Cr

Burlington®

Simply Exclusive Fabulous yet simplistic bathrooms

