



Handrinse basin, furniture handrinse basin # 0743500002

| < 500 mm > |



Handrinse basin, furniture handrinse basin	Dimension	Weight	Order number
with overflow, with tap platform, underneath glazed, 500 mm			
Colors			
00 White Alpin			
Variant			
●	500 x 400 mm	11.000 kg	0743500002
Suitable products			
Vanity unit wall-mounted 1 door, for Duravit No.1 # 074350, 440 x 386 mm	440 x 386 mm		N14267 L/R
Recommended faucets			
Single lever basin mixer S Ceramic cartridge, Projection 101 mm, Flexible connection hoses 3/8 ", aerator adjustable, Normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, with pop-up waste set,			B21010001
Single lever basin mixer S Ceramic cartridge, Projection 101 mm, Flexible connection hoses 3/8 ", aerator adjustable, Normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, without pop-up waste set,			B11010002
Single lever basin mixer S Ceramic cartridge, Projection 101 mm, Flexible connection hoses 3/8 ", aerator adjustable, Normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, with pop-up waste set,			B11010001
Single lever basin mixer S Ceramic cartridge, Projection 101 mm, Flexible connection hoses 3/8 ", aerator adjustable, Normal spray, chrome, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, without pop-up waste set,			B21010002
Single lever basin mixer S FreshStart Ceramic cartridge, in centre position cold water, projection 100 mm, Flexible connection hoses 3/8 ", flow rate 4,5 l/min (3 bar), Normal spray, connection size DN15, chrome, recommended operating pressure 3 - 5 bar, with pop-up waste set,			N11011001

Single lever basin mixer S FreshStart Ceramic cartridge, in centre position cold water, projection 100 mm, Flexible connection hoses 3/8 ",, flow rate 4,5 l/min (3 bar), Normal spray, connection size DN15, chrome, recommended operating pressure 3 - 5 bar, without pop-up waste set,	N11011002
Single lever basin mixer S MinusFlow Ceramic cartridge, projection 100 mm, Flexible connection hoses 3/8 ",, flow rate 3,5 l/min (3 bar), Normal spray, connection size DN15, chrome, recommended operating pressure 3 - 5 bar, with pop-up waste set,	N11012001
Single lever basin mixer S MinusFlow Ceramic cartridge, projection 100 mm, Flexible connection hoses 3/8 ",, flow rate 3,5 l/min (3 bar), Normal spray, connection size DN15, chrome, recommended operating pressure 3 - 5 bar, without pop-up waste set,	N11012002
Single lever basin mixer M Ceramic cartridge, projection 106 mm, Flexible connection hoses 3/8 ",, Normal spray, flow rate 5,0 l/min (3 bar), connection size DN15, chrome, recommended operating pressure 3 - 5 bar, without pop-up waste set,	N11020002
Single lever basin mixer M FreshStart Ceramic cartridge, in centre position cold water, projection 106 mm, Flexible connection hoses 3/8 ",, Normal spray, flow rate 5,0 l/min (3 bar), connection size DN15, chrome, recommended operating pressure 3 - 5 bar, with pop-up waste set,	N11021001
Single lever basin mixer M FreshStart Ceramic cartridge, in centre position cold water, projection 106 mm, Flexible connection hoses 3/8 ",, Normal spray, flow rate 5,0 l/min (3 bar), connection size DN15, chrome, recommended operating pressure 3 - 5 bar, without pop-up waste set,	N11021002
Single lever basin mixer M MinusFlow Ceramic cartridge, projection 106 mm, Flexible connection hoses 3/8 ",, Normal spray, flow rate 3,5 l/min (3 bar), connection size DN15, chrome, recommended operating pressure 3 - 5 bar, with pop-up waste set,	N11022001
Single lever basin mixer M MinusFlow Ceramic cartridge, projection 106 mm, Flexible connection hoses 3/8 ",, Normal spray, flow rate 3,5 l/min (3 bar), connection size DN15, chrome, recommended operating pressure 3 - 5 bar, without pop-up waste set,	N11022002
Single lever basin mixer S FreshStart Ceramic cartridge, in centre position cold water, projection 110 mm, Flexible connection hoses 3/8 ",, flow rate 5,0 l/min (3 bar), Normal spray, connection size DN15, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, with pop-up waste set,	TU1011001
Single lever basin mixer S FreshStart Ceramic cartridge, in centre position cold water, projection 110 mm, Flexible connection hoses 3/8 ",, flow rate 5,0 l/min (3 bar), Normal spray, connection size DN15, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, without pop-up waste set,	TU1011002
Single lever basin mixer S Ceramic cartridge, projection 110 mm, Flexible connection hoses 3/8 ",, flow rate 5,0 l/min (3 bar), Normal spray, connection size DN15, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, with pop-up waste set,	TU1010001

Single lever basin mixer S Ceramic cartridge, projection 110 mm, Flexible connection hoses 3/8 ", flow rate 5,0 l/min (3 bar), Normal spray, connection size DN15, maximum temperature can be adjusted on installation, recommended operating pressure 3 - 5 bar, without pop-up waste set,	TU1010002
Single lever basin mixer S Ceramic cartridge, projection 100 mm, Flexible connection hoses 3/8 ", flow rate 5,0 l/min (3 bar), Normal spray, connection size DN15, chrome, recommended operating pressure 3 - 5 bar, with pop-up waste set,	N11010001
Single lever basin mixer S Ceramic cartridge, projection 100 mm, Flexible connection hoses 3/8 ", flow rate 5,0 l/min (3 bar), Normal spray, connection size DN15, chrome, recommended operating pressure 3 - 5 bar, without pop-up waste set,	N11010002

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.