
# Geberit Monolith sanitary module for floor-standing WC, 114 cm













# **Application purposes**

- · For floor inlets
- · For renovations, conversions and new buildings
- For wall inlets with an inlet height of 18 cm
- For replacing floor-standing WCs with concealed cistern with maximum service opening height < 109 cm</li>
- · For replacing low-level exposed cisterns
- For replacing half-high level exposed cisterns
- For replacing floor-standing WCs with close-coupled exposed cistern
- For connecting Geberit AquaClean Sela floor-standing WC
- For connecting Geberit AquaClean Tuma WC complete solution, floor-standing WC
- For connecting Geberit AquaClean WC enhancement solutions, with accessories
- For replacing pressure flushing valves
- · For mounting on finished floors
- · For installation in front of drywalls or solid walls

# Characteristics

- Dual flush
- Compensation of dimensional tolerances possible
- Front cladding made of glass (ESG)
- · Cistern fully insulated against condensation
- · Side cladding made of aluminium brushed
- Self-supporting

- · Adjustable flush volume
- · Water supply connection on the rear centre
- Water supply connection on the left/right possible with accessories
- Water supply connection on the bottom

#### **Technical data**

Flow pressure	0.1-10 bar
Maximum operating temperature, water	25 ℃
Flush volume, factory setting	6 and 3 l
Flush volume large, adjustment range	4.5 / 61
Flush volume small	31
Calculated flow rate	0.11 l/s
Minimum flow pressure for calculated flow rate	0.5 bar

# Scope of delivery

- Water supply connection set with 2 angle stop valves, 1/2"
- Flush bend extension 160 mm
- Connection bend made of PP, ø 90 mm
- Sleeve made of EPDM, ø 44 / 55 mm
- Adaptor socket made of PE-HD, ø 90 / 110 mm
- · Fastening material
- Base cover
- · Fastening material for drywall

Art. no.	Surface / colour
131.033.SQ.5	glass / umber
131.033.SI.5	glass / white
131.033.TG.5	glass / sand
131.033.SJ.5	glass / black



# Accessories

- Set of fixing bolts made of aluminium, for Geberit Monolith side cladding
- Conversion set for Geberit AquaClean WC enhancement solutions
- Lateral water supply connection set for Geberit Monolith sanitary module for WC



Glass thickness 8 mm