


## Geberit Monolith sanitary module for wall-hung WC, 101 cm



### Application purposes

- For renovations, conversions and new buildings
- For wall inlets with inlet height > 23 cm
- For replacing low-level exposed cisterns
- For replacing wall-hung WCs with close-coupled exposed cistern
- For Geberit AquaClean WC complete solutions
- For connecting Geberit AquaClean WC enhancement solutions, with accessories
- For mounting on finished floors
- For installation in front of drywalls or solid walls
- For compensating the offset between WC connections and wall drains using a stepped straight connector for wall-hung WCs

### Characteristics

- Dual flush
- Compensation of dimensional tolerances possible
- Height-adjustable up to 7 cm
- Front cladding made of glass (ESG)
- Fastening height WC ceramic appliance  $35 \pm 1$  cm
- Cistern fully insulated against condensation
- Side cladding made of aluminium brushed
- Self-supporting

- Adjustable flush volume
- Water supply connection on the bottom
- Water supply connection on the left/right possible with accessories

### Technical data

Flow pressure	0.1-10 bar
Maximum operating temperature, water	25 °C
Flush volume, factory setting	6 and 3 l
Flush volume large, adjustment range	4.5 / 6 l
Flush volume small	3 l

### Scope of delivery

- Water supply connection set with 2 angle stop valves, 1/2"
- Flush bend extension 160 mm
- Sleeve made of EPDM,  $\varnothing 44 / 55$  mm
- Straight connector made of PE-HD,  $\varnothing 90$  mm
- Adaptor socket made of PE-HD,  $\varnothing 90 / 110$  mm
- 2 threaded rods M12
- Sound insulation set
- Base cover
- Fastening material for drywall
- Fastening material

Art. no.	Surface / colour
131.021.SL.5	glass / mint
131.021.SJ.5	glass / black
131.021.SI.5	glass / white
131.021.TG.5	glass / sand
131.021.SQ.5	glass / umber

### Accessories

- Geberit straight connector set for wall-hung WC, stepped by 3 cm

- Geberit connection set for wall-hung WC, with straight connector stepped by 5 cm
- Geberit straight connector set for wall-hung WC, stepped by 7 cm
- Set of fixing bolts made of aluminium, for Geberit Monolith side cladding
- Lateral water supply connection set for Geberit Monolith sanitary module for WC
- Conversion set for Geberit AquaClean WC enhancement solutions



- 
- Glass thickness 8 mm, Mint colour glass thickness 6 mm