


# Geberit Duofix element for wall-hung WC, 98 cm, with Delta concealed cistern 12 cm, Delta30 actuator plate





Example image

## Application purposes

- For drywall construction
- · For installation in part-height prewall installations
- For wall-hung WCs with connection dimensions in accordance with EN 33:2011
- For wall-hung WCs with projection up to 62 cm
- For floor constructions 0–20 cm

## Characteristics

- Statically self-supporting frame, protected against corrosion with powder coating
- Frame top openFrame with ø 9 mm drilling holes for fastening in wood frame

# • Feet adjustable 0-20 cm

- Foot plates made of plastic
- Foot plate depth suitable for installation in U-profiles UW 50
- Connection bend can be mounted without tools
- Concealed cistern with front actuation
- Concealed cistern, fully insulated against condensation
- Cistern fulfils standard requirements in accordance with EN 14055, Class II
- · Immediate post flush possible with factory setting
- · Water supply connection on the rear or top centre
- With conduit pipe for feed pipe for Geberit AquaClean shower toilets and for connection cable
- · Fastening option for electrical connection

#### **Technical data**

small contact surfaces   F     • Galvanized feet   F     Scope of delivery   • Angle stop valve R 1/2", compatible with MF, with adapter ring   • C	Dperating temperature, water max. Flush volume, factory setting Flush volume small, adjustment range	25 °C 5.8/31 2–41
Galvanized feet G	lush volume small, adjustment range	
F     Scope of delivery     • Angle stop valve R 1/2", compatible with MF, with adapter ring     • C		2-41
Angle stop valve R 1/2", compatible with MF, with adapter ring O		
2 distance bolts Delta30 actuator plate 2	Connection bend 90° made of PE-HD, ø 90 mm Adaptor socket made of PE-HD, ø 90 / 110 mm 2 protection plugs 2 threaded rods M12 Fastening material	

Art. no.	Colour / surface	В	Н	Т	
458.152.21.1	gloss chrome-plated	50 cm	98 cm	12 cm	New

### Accessories

· Geberit set of support brackets for WC ceramic appliances with small contact surfaces