



# Geberit Duofix element for wall-hung WC, 79 cm, with low-height concealed cistern



## APPLICATION PURPOSES

- For metal and wood frame walls
- For installation in part-height prewalls
- For installation in bathroom furniture
- For floor constructions 0-18 cm
- For wall-hung WCs
- Not suitable for Geberit AquaClean Alba
- Not suitable for Geberit AquaClean Sela

## CHARACTERISTICS

- 2025 range

- Statically self-supporting frame, protected against corrosion with powder coating
- Frame for wall-hung WCs with connection dimensions as per EN 33 and projection up to 62 cm
- With large foot plates for raised power supply in floors
- Galvanised leg supports protected against corrosion
- Connection bend can be mounted without tools
- Cistern with low installation height
- Pneumatic flush actuation, suitable for dual flush
- Flush pipe connection with compression joint
- Water supply connection on the bottom left
- Water supply connection 1/2"

## TECHNICAL DATA

Flow pressure	0.1-10 bar
Water temperature max.	25 °C
Flush volume, factory setting	5.8 / 3 l
Product material	Steel
Height-adjustable	Yes

## ACCESSORIES

- Geberit set of support brackets for WC ceramic appliances with small contact surfaces

Art. no.	B cm	H cm	T cm
111.207.00.3	46.5	79	19.5-31.5