

Geberit Alpha concealed cistern 12 cm, 5.8 / 3 litres, installation height 109 cm







APPLICATION PURPOSES

- For masonry walls
- For installation in part or room-height prewall installations
- For installation in room-height installation walls
- For floor-standing and wall-hung WCs

CHARACTERISTICS

- Adjustable in depth
- Geberit Alpha concealed cistern 12 cm fully insulated against condensation
- For front actuation, suitable for dual flush
- Immediate post flush possible with factory setting
- Cistern fulfils standard requirements in accordance with EN 14055, Class II
- Flush bend fitted
- Water supply connection on the rear or top centre
- Protection box for service opening, can be cut to length, protects against moisture and dirt

TECHNICAL DATA

Flow pressure	0.1–10 bar
Water temperature max.	25 °C
Flush volume, factory setting	5.8 / 3 l
Flush volume large, adjustment range	4 / 4.5 / 6 / 7.5 l
Flush volume small, adjustment range	2–4 l
Product material	Plastic

SCOPE OF DELIVERY

- Water supply connection unit R 1/2", compatible with MasterFix and MeplaFix, with integrated angle stop valve and adapter ring
- Protection box for service opening
- Fastening for flush bend
- Flush bend extension, ø 45 mm
- 2 fixing brackets
- Fastening and protection material

Art. no.	B cm	H cm	T cm
109.012.00.1	44	39.5	12