



## Geberit Sigma concealed cistern 8 cm, 6 / 3 litres



Example image



### Application purposes

- For drywall construction
- For masonry walls
- For installation in part or room-height prewall installations
- For floor-standing WCs

### Characteristics

- Concealed cistern with front actuation
- Concealed cistern, fully insulated against condensation
- Cistern fulfils standard requirements in accordance with EN 14055, Class II
- Immediate post flush possible with factory setting
- Flush bend fitted

- Tool-free installation and maintenance work on concealed cistern
- Water supply connection on the top left
- Protection cover box for service opening protects against moisture and dirt
- Protection box for service opening can be cut to length, suitable for surface-even flush plates

### Technical data

|                                      |             |
|--------------------------------------|-------------|
| Flow pressure                        | 0.1-10 bar  |
| Maximum operating temperature, water | 25 °C       |
| Flush volume, factory setting        | 5.8 and 3 l |
| Flush volume small, adjustment range | 3-4 l       |

### Scope of delivery

- Water supply connection Rp 1/2" - R 1/2", compatible with MF, with integrated angle stop valve and hand wheel
- Protection box for service opening
- Flush bend 90°
- Fastening for flush bend
- Protection plug
- Cup for flush volume reduction 4.5 / 3 l
- Fastening material
- 2 fixing brackets

| Art. no.     | B     | H       | T    |
|--------------|-------|---------|------|
| 109.792.00.1 | 41 cm | 62.5 cm | 8 cm |



- Flush valve features settings to enable either a 6 l and 3 l flush or a 4.5 l and 3 l flush. Note: must be used with pans designed for low volume flush.
- The cistern can be operated with used water (rainwater) provided it is passed through a filter system first