







## Product Description: Rapid SL 3-in-1 set for WC

# Standard Specification: flushing cistern GD 2

with small maintenance access

#### 1.13 m installation height

for on-the-wall installations or studded walls powder coated steel frame, self-supporting for dry-cladding, completely pre-assembled with fixed connections for single or rail installation quick adjustment, lockable fixing material

TÜV approved

2 WC fixing bolts

fixing device for ceramic

WC ceramics with small bearing area (less than 205 mm)

require additional accessory 38 779 000

distance of fixing bolts 180/230 mm

outlet bend Ø 90 mm

depth adjustable

reducer Ø 90/110 mm

inlet and outlet connecting set

#### flushing cistern GD 2, 6 - 9 I

adjustment ex factory 6 I and 3 I

water supply from left/right or back

pneumatic discharge valve offering 3 modes of

operation: dual flush or start/stop or single flush

low noise (group I acc. to German Noise Specification)

insulated against condensation

½" water supply connection including integrated

angle valve and push fit flexible hose union

no tools required for the installation of the inspection shaft

including protection during construction phase

for vertical or horizontal use

accessories for on-the-wall installation

with GROHE Fresh retrofit set

### including flush plate Nova Cosmopolitan

for dual flush or start & stop actuation vertical and horizontal installation 156  $\times$  197 mm

chrome

made of ABS

**GROHE StarLight** chrome finish



Color:

□ 38860000 chrome