







## Product Description: Rapid SL 4-in-1 set for WC

# Standard Specification: flushing cistern GD 2

with small maintenance access

#### 1.13 m installation height

for on-the-wall installations or studded walls powder coated steel frame, self-supporting for dry-cladding, completely pre-assembled with fixed connections for single or rail installation quick adjustment, lockable fixing material TÜV approved

2 WC fixing bolts fixing device for ceramic

WC ceramics with small bearing area (less than 205 mm)

require additional accessory 38 779 000 distance of fixing bolts 180/230 mm

outlet bend Ø 90 mm

depth adjustable

reducer Ø 90/110 mm

inlet and outlet connecting set

#### flushing cistern GD 2, 6 - 9 I

adjustment ex factory 6 I and 3 I

pneumatic discharge valve offering 3 modes of operation: dual flush or start/stop or single flush

water supply from left/right or back

low noise (group I acc. to German Noise Specification)

insulated against condensation

½" water supply connection including integrated angle valve and push fit flexible hose union

no tools required for the installation of the inspection shaft including protection during construction phase

for vertical or horizontal use

### including flush plate Skate Air

for dual flush or start & stop actuation vertical installation

156 x 197 mm

chrome

made of ABS

**GROHE StarLight** chrome finish accessories for on-the-wall installation

with GROHE Fresh retrofit set

Pure Freude an Wasser



□ 38884000