

11 815 2 **RAPID SL 3 IN 1 SET FOR WC**



PRODUCT DESCRIPTION (1/2)

- with flush cistern 6 - 3 l
- 1.0 m finished installation height
- for on-the-wall installations or studed walls
- powder coated steel frame, self-supporting
- for dry-cladding, completely pre-assembled
- with fixed connections
- quick adjustment, lockable
- 2 WC fixing bolts
- fixing material
- TÜV approved
- fixing device for ceramic
- distance of fixing bolts 180/230 mm
- outlet bend Ø 90 mm
- depth adjustable
- reducer Ø 90/110 mm
- inlet and outlet connecting set
- flushing cistern 6 - 9 l
- pneumatic discharge valve offering 2 modes of operation: dual flush or single flush
- front/top actuation
- water supply from left/right or back
- low noise (group I acc. to German Noise Specification)
- Insulated against condensation
- ½" water supply connection including integrated angle valve and push fit flexible hose union
- protecting block
- with wall brackets for on-the-wall installations
- Skate Cosmopolitan flush plate
- for horizontal installation
- 156 x 197 mm
- chrome
- made of ABS
- GROHE Water Saving - Less water, perfect flow

Pure Freude
an Wasser



11 815 2 **RAPID SL 3 IN 1 SET FOR WC**

PRODUCT DESCRIPTION (2/2)

- GROHE Long-Life finish