

shower valves - Puro Thermostatic Shower

Bringing inspiration,
performance
and peace of mind,
protection

Introduction

The all new Puro collection from Inta is defined by the unique contemporary styling of the handles, oversized soaker and multi-function eco air handset. The Puro range is the ultimate combination of form and function featuring safe touch surface valve bodies and Inta's proven anti-scald thermostatic technology. Bring inspiration, performance and peace of mind protection to your bathroom with Inta's Puro range.



PU90015CP

- Operating pressure range of 0.2 to 5 bar
- Slim eco air handset
- Safe touch body
- Thermal cartridge technology
- Temperature stability of $\pm 2^{\circ}\text{C}$
- Fail safe on hot and cold supplies
- Suitable for use with unvented supplies, combi boilers, gravity and mains pressure systems

Product Range

Description	Code
Puro thermostatic bath shower mixer, slide rail kit, eco air handset and deck mounting legs.	PU90015CP



shower valves - Puro Thermostatic Shower

■ Technical Specification

Max Inlet Pressure static	5 Bar
Min Inlet Pressure dynamic	0.2 Bar
Max Inlet Temperature	85°C
Factory Pre-set Temperature	38°C with max temp stop
Inlet Connections for PU90015CP	G 3/4" F BSP
Outlet Connections	G 1/2" BSP (bottom)
Min Temperature to achieve hot or cold failsafe	15°C
System Installation	Unvented, Pressurised, Gravity and Combination Boilers

