

Enzo Thermostatic Shower

Introduction:

The new Enzo range from Inta is a real best seller. Beautifully subtle curved lines and simple form belie the technology that is packed into each shower. Enzo is both safe to touch during operation and thermostatically controlled so that it protects from delivering water that is hot enough to scald.



- Anti-scald thermostatic technology with fail safe protection on both the hot and cold supplies
- Suitable for use with unvented supplies, combi boilers, gravity and mains pressure systems
- WRAS and TMV2 approved valve
- High flow rates
- Stylish ergonomic metal handles
- Range of soakers and risers available

Product Range

Description	Code
Enzo Concealed Thermostatic Shower Single Outlet	EN40010CP
Enzo Concealed Thermostatic Shower Dual Outlet	EN80010CP



Enzo Thermostatic Shower

Technical Specification

Max Inlet Pressure static :	5 Bar
Min Inlet Pressure dynamic :	0.2 Bar
Max Inlet Temperature :	85°C
Factory Pre-set Temperature :	38°C with max temp stop
Inlet Connections with Fast Fix :	G 1/2"
Outlet Connections :	G 1/2" BSP
Min Temperature to achieve hot or cold failsafe :	15°C
System Installation :	Unvented, Pressurised, Gravity and Combination Boilers

