Code


5161CP



Inta Spouts



Robust construction






Description Inta wall mounted fixed basin spout

MIN OPERATING PRESSURE: 0.5 BAR DYNAMIC

■ MAX OPERATING PRESSURE: 5 BAR STATIC

■ MAX INLET TEMPERATURE: 65°C

Product Range






Product Range

Description	Code
Inta wall mounted fixed minimalistic spout	5165CP


MIN OPERATING PRESSURE: 0.5 BAR DYNAMIC
 MAX OPERATING PRESSURE: 5 BAR STATIC

■ MAX INLET TEMPERATURE: 65°C










Product Range

Description	Code
Inta wall mounted spout	5287CP

- MIN OPERATING PRESSURE: 0.5 BAR DYNAMIC
- MAX OPERATING PRESSURE: 5 BAR STATIC
- MAX INLET TEMPERATURE: 65°C



Description	Code
Inta basin mounted fixed bast spout	5163CP


- MIN OPERATING PRESSURE: 0.5 BAR DYNAMIC
- MAX OPERATING PRESSURE: 5 BAR STATIC
- MAX INLET TEMPERATURE: 65°C











Product Range

Description	Code
Inta basin mounted fixed spout	5160CP

- MIN OPERATING PRESSURE: 0.5 BAR DYNAMIC
- MAX OPERATING PRESSURE: 5 BAR STATIC
- MAX INLET TEMPERATURE: 65°C

Product Range

Description	Code
Into basin mounted swivel tube spout	5162CP

- MIN OPERATING PRESSURE: 0.5 BAR DYNAMIC
- MAX OPERATING PRESSURE: 5 BAR STATIC
- MAX INLET TEMPERATURE: 65°C

