# Aquaflow 3 Single Lever



Product finish	Chrome
Product category	Single Lever
First supplied date	

EAN 13 barcode	5015834045665
Location of DOM trace code:	DOM code on multiple box outer




#### **Product features:**

- Metal & ABS construction
- · Custom designed for lower to mid pressures
- Single lever control for effortless single handed control
- Supplied compete with flexible tail pipes for fast simple fitting
- · Classic European design styling

Additional information / Parts included:

Nb. Model shown may not be displayed in the finish as described.

### Product dimensions & valve type:



• Overall Height / projection: 145 mm

• Exit reach: 230 mm • Exit height: 122 mm

• Centre distance(s): N/A mm

• Base diameter(s): 53 mm

• Recommended fixing hole diameter: Ø35 mm


• Max. surface fixing depth: 50 mm

• Control valve type: 40mm Ø Ceramic single lever

• Valve detail: N/A

• DDA compliant design? Yes

### **Product flow characteristics:**



- Min / Max water pressure: 0.30 / 5.50 bar (LP)
- Recommended / Maximum water temperature: 46°C / 70°C

#### • Part G:

Unrestricted mixed flow rate, 3 bar (litres / min): 19.83

\*Flow results are produced under test conditions and represent the non flow regulated dynamic output of the product model.

LP (lower pressure) less than 0.5 bar MP (medium pressure) 0.5 bar to 1 bar HP1 (high pressure) 1 bar to 2 bar HP2 (very high pressure) 2 bar or more

Minimum flow rate (1 GPM) based on mixed flow.

## TAF3CM/

# Aquaflow 3 Single Lever



#### Flow regulator included? N/A

#### Inlet pipes:

• Tail pipe inlet / outlet size: M12x1 / 1/2" Male / 15mm ID with 2 x 15mm nuts and olives

• Inlet pipe type / length: Flexible stainless braided hose / 320 mm

#### Spout detail & Flow characteristics:

Spout diameter: 15x8 mm
Spout aerator size: M24x1 M
Spout rotation range: 360°
Aerator type: Flow straightener
Aerator colouring: White plastic

• Spout connection: Base plinth removes

• Product flow characteristics: Single flow

• Non return valve (NRV) supplied: No, None suppled

• NRV required to be installed for byelaw compliance:

Yes, on both hot & cold supplies

#### **Product markings and indicators:**

• Branding position: None

• Hot / Cold indication: Red & Blue Split Plastic Indices

Packaged properties:	
Box length: 310 mm	Box depth: 70 mm
Box width: 130 mm	Units per outer: 10
Box has 'pressure warning sticker' ?	No
Packaging branding:	White unprinted

Tap only weight: 0.62 kg	
Boxed weight: 1.00 kg	
Total card weight: 122 grams	
Total plastics weight: 11 grams	

- Approval certificate number:
- · Expiry date:

#### Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 2 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 years

#### Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives