

# K RAIL 22

**MODERN  
CONTEMPORARY  
DESIGN**

**DELIVERY  
CODE  
A**

THIS ITEM NORMALLY  
DISPATCHED WITHIN  
48 HOURS OF ORDER



**Height: 800mm**  
Tube diameter: 22mm  
Width: 400, 500, 600mm  
No. of Crossrails: 14  
Style: Straight, Curved  
Finish: Chrome

**Height: 1000mm**

Tube diameter: 22mm  
Width: 400, 500, 600mm  
No. of Crossrails: 16  
Style: Straight, Curved  
Finish: Chrome



**Height: 1200mm**

Tube diameter: 22mm  
Width: 400, 500, 600mm  
No. of Crossrails: 20  
Style: Straight, Curved  
Finish: Chrome

**Height: 1600mm**

Tube diameter: 22mm  
Width: 400, 500, 600mm  
No. of Crossrails: 26  
Style: Straight, Curved  
Finish: Chrome



**Height: 1800mm**

Tube diameter: 22mm  
Width: 500, 600mm  
No. of Crossrails: 31  
Style: Straight, Curved  
Finish: Chrome

**EXTENDED RANGE  
300mm & WHITE RAILS**

# K RAIL 22

## Product Features

SIZES	MATERIAL	COLOUR	PRESSURE TESTED TO	GUARANTEE
28	S	CHR	10 BAR	5 YEARS



## K RAILS Standard Product Range



- Standard rails 22mm tube diameter
- Available as straight or curved
- Sparkling highly polished chrome finish or a classic brilliant ice white
- Supplied complete with fixing kit, including plugs and vents
- Manufactured under BS EN ISO 9001 quality standards
- Pressure tested to 10 bar / maximum working pressure 7 bar

Ø 25mm Straight						
Width (mm)	Height (mm)	C/C Tappings (mm)	Headers Dimensions (mm)	Quantity of Cross Rails	Tube Ø (mm)	Summer Element Watts
300	800	255	30/40/1.5	14	Ø22	300
300	1000	255	30/40/1.5	16	Ø22	300
300	1200	255	30/40/1.5	20	Ø22	300
300	1600	255	30/40/1.5	26	Ø22	500
400	800	355	30/40/1.5	14	Ø22	300
400	1000	355	30/40/1.5	16	Ø22	300
400	1200	355	30/40/1.5	20	Ø22	500
400	1600	355	30/40/1.5	26	Ø22	500
500	800	455	30/40/1.5	14	Ø22	300
500	1000	455	30/40/1.5	16	Ø22	300
500	1200	455	30/40/1.5	20	Ø22	500
500	1600	455	30/40/1.5	26	Ø22	500
500	1800	455	30/40/1.5	31	Ø22	500
600	800	555	30/40/1.5	14	Ø22	300
600	1000	555	30/40/1.5	16	Ø22	300
600	1200	555	30/40/1.5	20	Ø22	500
600	1600	555	30/40/1.5	26	Ø22	500
600	1800	555	30/40/1.5	31	Ø22	800

CHROME				
Output ΔT50°C				
Code	Watts	BTUs	Delivery Code	Price (£)
STR308C	222	757	A	£106.41
STR310C	264	902	A	£124.89
STR312C	322	1,098	A	£139.16
STR316C	425	1,452	A	£170.68
STR408C	255	870	A	£112.61
STR410C	304	1,037	A	£132.15
STR412C	370	1,262	A	£147.26
STR416C	489	1,668	A	£180.62
STR508C	302	1,030	A	£121.10
STR510C	357	1,218	A	£144.05
STR512C	436	1,488	A	£161.80
STR516C	576	1,965	A	£197.60
STR518C	662	2,259	A	£248.63
STR608C	350	1,194	A	£129.63
STR610C	413	1,409	A	£149.21
STR612C	506	1,726	A	£172.13
STR616C	668	2,279	A	£210.34
STR618C	768	2,620	A	£271.58

WHITE				
Output ΔT50°C				
Code	Watts	BTUs	Delivery Code	Price (£)
STR308W	316	1,079	A	£73.43
STR310W	377	1,286	A	£86.17
STR312W	459	1,565	A	£96.02
STR316W	606	2,068	A	£117.77
STR408W	363	1,240	A	£77.70
STR410W	433	1,478	A	£91.19
STR412W	527	1,799	A	£101.61
STR416W	697	2,378	A	£124.63
STR508W	430	1,468	A	£83.56
STR510W	509	1,736	A	£99.39
STR512W	621	2,120	A	£111.64
STR516W	821	2,801	A	£136.34
STR518W	943	3,219	A	£171.55
STR608W	499	1,702	A	£89.44
STR610W	589	2,008	A	£102.96
STR612W	721	2,460	A	£118.77
STR616W	952	3,248	A	£145.13
STR618W	1,094	3,734	A	£187.39

Ø 22mm Curved						
Width (mm)	Height (mm)	C/C Tappings (mm)	Headers Dimensions (mm)	Quantity of Cross Rails	Tube Ø (mm)	Summer Element Watts
300	800	255	30/40/1.5	14	Ø22	300
300	1000	255	30/40/1.5	16	Ø22	300
300	1200	255	30/40/1.5	20	Ø22	300
300	1600	255	30/40/1.5	26	Ø22	500
400	800	355	30/40/1.5	14	Ø22	300
400	1000	355	30/40/1.5	16	Ø22	300
400	1200	355	30/40/1.5	20	Ø22	500
400	1600	355	30/40/1.5	26	Ø22	500
500	800	455	30/40/1.5	14	Ø22	300
500	1000	455	30/40/1.5	16	Ø22	300
500	1200	455	30/40/1.5	20	Ø22	500
500	1600	455	30/40/1.5	26	Ø22	500
500	1800	455	30/40/1.5	31	Ø22	500
600	800	555	30/40/1.5	14	Ø22	300
600	1000	555	30/40/1.5	16	Ø22	300
600	1200	555	30/40/1.5	20	Ø22	500
600	1600	555	30/40/1.5	26	Ø22	500
600	1800	555	30/40/1.5	31	Ø22	800

CHROME				
Output ΔT50°C				
Code	Watts	BTUs	Delivery Code	Price (£)
CTR308C	222	757	A	£112.80
CTR310C	264	902	A	£132.38
CTR312C	322	1,098	A	£147.51
CTR316C	425	1,452	A	£180.92
CTR408C	255	870	A	£119.84
CTR410C	304	1,037	A	£140.08
CTR412C	370	1,262	A	£156.10
CTR416C	489	1,668	A	£187.85
CTR508C	302	1,030	A	£128.33
CTR510C	357	1,218	A	£152.69
CTR512C	436	1,488	A	£171.51
CTR516C	576	1,965	A	£204.83
CTR518C	662	2,259	A	£263.54
CTR608C	350	1,194	A	£136.82
CTR610C	413	1,409	A	£158.17
CTR612C	506	1,726	A	£182.45
CTR616C	668	2,279	A	£217.57
CTR618C	768	2,620	A	£287.87

WHITE				
Output ΔT50°C				
Code	Watts	BTUs	Delivery Code	Price (£)
CTR308W	316	1,079	A	£77.83
CTR310W	377	1,286	A	£91.34
CTR312W	459	1,565	A	£101.78
CTR316W	606	2,068	A	£124.84
CTR408W	363	1,240	A	£82.69
CTR410W	433	1,478	A	£96.66
CTR412W	527	1,799	A	£107.71
CTR416W	697	2,378	A	£129.61
CTR508W	430	1,468	A	£88.55
CTR510W	509	1,736	A	£105.36
CTR512W	621	2,120	A	£118.34
CTR516W	821	2,801	A	£141.33
CTR518W	943	3,219	A	£181.84
CTR608W	499	1,702	A	£94.41
CTR610W	589	2,008	A	£109.13
CTR612W	721	2,460	A	£125.89
CTR616W	952	3,248	A	£150.12
CTR618W	1,094	3,734	A	£198.63

Notes: • C/C Tappings = Distance between tapping centre • Outputs quoted are based on a mean water temperature of 70°C and a room temperature of 20°C.  
Wall to C/C tappings; Straight = 64-86mm adjustable. Curved = 52-74mm adjustable.