Thermostat Operating Manual

1. General Introduction

- a .Operating Voltage: 230V/50Hz
- b. Heating Element Power: 200W-1000W
- c. Operating Ambient Temperature: 0~55℃
- d. Temperature Setting Range: $30 70^{\circ}$ C (5 $^{\circ}$ C every change)
- e. MODES: Standby/Thermostatic Work /2H/4H/6H/8H Timer
- f. With Memory Mode.
- g. Insulation Class: Class I
- h. IP Degree of Protection: IPX4
- i. Size:70 x 60 x 45 mm

2. LED Screen:



3. Buttons:



4. Status and Modes displayed on LED Screen

4.1 Standby Mode

The device enters into standby mode when the power is switched on, in this mode a continuous "●" flashing on the screen.



4.2 Power On

4.2.1 Thermostatic Heating Mode: the LED screen shows the temperature setting value,

the temperature value flashes when heating, it stops flashing when heating is done.

4.2.2 2 Hours Heating Mode: LED screen shows

4.2.3 4 Hours Heating Mode: LED screen shows

4.2.4 6 Hours Heating Mode: LED screen shows

4.2.5 8 Hours Heating Mode: LED screen shows

Mode Operating Instruction: 5.

5.1 Enter Into Work Mode: press button briefly to enter into WORK mode; Or press button briefly in STANDBY mode, enter into 2 HOURS HEATING mode (must be power on);

5.2 Switching Between Modes: press button 0 briefly to switch the mode from STANDBY mode to THERMOSTATIC HEATING mode, and then press button to switch to TIME HEATING mode. When requesting to switch the mode from TIME

HEATING mode to THERMOSTATIC HEATING mode, press button briefly to STANDBY mode first, and then press button (2) again to switch to THERMOSTATIC HEATING mode.

5.2.1 Thermostatic Heating Mode: press button ^(U) briefly to change STANDY BY mode to THERMOSTATIC HEATING mode, press button 🛨 or briefly to set the







temperature, temperature range can be set between $30 \sim 70$ °C, 5 °C every change.

5.2.2 Time Heating Mode:

- A: Press button briefly to switch the STAND BY mode into 2 HOURS HEATING mode, and then press again. The mode can be changed between STAND $BY\rightarrow 2H\rightarrow 4H\rightarrow 6H\rightarrow 8H\rightarrow STAND$ BY, the device will go back to STAND BY mode when TIME HEATING mode process is done.
- B: In THERMOSTATIC HEATING mode, press button \bigcirc briefly to enter into 2 HOURS HEATING mode, and then press \bigcirc button to change between STAND BY \rightarrow 2H \rightarrow 4H \rightarrow 6H \rightarrow 8H \rightarrow STAND BY, the device will go back to THERMOSTATIC HEATING mode when TIME HEATING mode process is done.

5.3 Power Off

5.3.1 In Power On status, press button ^(U) briefly to turn off the device.

6. Over Temperature Protection

When temperature exceeds 85° C or is lower than -25°C, the device shuts down automatically. And symbol "Er" appears on display.

-