

Mira Extra

Thermostatic BSM



SUITABLE FOR ALL SYSTEMS



5 YEAR WARRANTY

Experience safer showering with this thermostatically controlled shower combined with bathfill. It's made great showering simple.

Product Information

Description	Colour	Product No.
Mira Excel BSM	Chrome	1.0.122.25.2

Features & Benefits

Temperature control

Thermostatic temperature stability (shower & bathfill)

Easy to fit

Fits onto standard bath tap holes

Easy to service

Replaceable cartridge with integral filters

For your customer

One control for on/off and temperature

A convenient, alternative way of showering

4 spray 9cm showerhead with rub-clean nozzles



Product Specification

Tech Details

Temperature control

Control type: Thermostatic shower control

Installation

Water entry points: Rising only

Inlet connections: 3/4" BSP Male

Outlet connections: 1/2" BSP Male

Reversed inlets supported: No = hot left, cold right only

Supply Conditions (hot and cold)

Cold water range: Up to 25°C

Hot water range: 50°C-85°C (operating)
55°C-65°C (recommended)

Minimum maintained pressure: 0.1 bar (1 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

Performance

Flow rate (at handset): 15 l/min at 0.5 bar

Temperature stability: $\pm 2^{\circ}\text{C}$

Safety Features

Automatic shutdown: Shutdown within 2 secs (shower only)

Factory set to safe max temp: Factory set to 42°C

Adjustable maximum temperature for on-site conditions

Dimensions

