geo6 bi-fold door

consists of 2 folding door panels 6mm toughened safety glass spring loaded door buffer for soft closing



Geo6 bi-fold door

to specify/order:

Please use the product reference shown below.

bi-fold door

900mm, LH or RH G65200CP 800mm, LH or RH G64200CP G63200CP 760mm, LH or RH

side panel (including towel rail)Side panel 900mm **G65500CP** Side panel 800mm G64400CP Side panel 760mm G63400CP (Above supplied with standard wall profiles that give 25mm adjustment)

in-line panels

Refer to main product page for details.

Please refer to shower trays.

extension profile

Extension profile for extra 30mm adjustment

G60600CP

material


Aluminium frame, 6mm toughened safety glass.


finish/colour

Polished silver frame, clear glass.

Can be installed to open from left or right.

Product Number	Description	W - Width mm	E - Entry Width mm	SI - Swing Inwards mm	Adjustment Range mm	Adjustment With Side Panel mm
G63200CP	Bi-Fold Door 760mm	760	365	255	710-760	732-760
G64200CP	Bi-Fold Door 800mm	800	415	275	750-800	772-800
G65200CP	Bi-Fold Door 900mm	900	515	320	850-900	872-900
G63400CP	Side Panel 760mm	760	N/A	N/A	730-755	N/A
G64400CP	Side Panel 800mm	800	N/A	N/A	770-795	N/A
G65500CP	Side Panel 900mm	900	N/A	N/A	870-895	N/A





All measurements shown are in millimetres. Drawing sizes

