


Installation instructions for Shaver Socket SY9660CC

WARNINGS

- Please read these instructions carefully before commencing any work
- This product should be installed and wired by a qualified electrician in accordance with the current IEE regulations and must be protected by a RCD device.
- Ensure the power supply is disconnected before proceeding with the installation
- This product must be earthed
- All bare earth wires must be covered with appropriate green/yellow sleeving, not supplied
- Please check with manufacturers instruction for suitability with rechargeable shavers

Installation

Installation

- This shaver supply unit is suitable for surface mounting, using a 49mm 2 gang surface back box or flush mounting using a 47mm 2 gang metal back box
 - Remove and retain the 2 fixing screws located at the back of the fascia plate
 - Feed supply cable through the appropriate knockout installation box. In the case of a metal back box fit a 20mm rubber grommet
 - Strip outer sheath of supply cable to suitable length and then remove 10mm of the insulation from the Live (brown) and Neutral (blue) conductors to expose inner cores
 - Insert Neutral (blue) conductor into the terminal marked N and fully tighten the screw
 - Insert Live (brown) conductor into the terminal marked L and fully tighten the screw
 - Insert the earth conductor, ensuring it has been sleeved with green/yellow sleeving, into the terminal marked 
 - Ensure that an additional earth cable is connected between the shaver supply unit earth terminal and the earth terminal in the back box being used
 - Fit socket to back box with the 2 fixing screws provided
 - Re-fit the supply fuse (if removed) for isolation and switch supply back on
- Select voltage required 115V/230V by inserting shaver plug into the appropriate socket
- Always unplug appliance after use

Installation

