



## Jaguar Thermostatic Radiator Valve - Corner



Available Finishes	
Chrome	Brushed (Satin) Nickel
Antique Brass	Black Nickel
Antique Copper	Brass

Connection Size	
Valve to Radiator	1/2" BSPT
Valve to Pipe	15 mm Compression

Allen Key size	
To adjust Lock-Shield	SW8
To fit Coupler to Radiator	SW13
Allen Keys are not included	

Pressure Ratings	
Max Test Pressure	16 Bar
Max Operating Pressure	10 Bar
Max Differential Pressure	1 Bar
Pressure Drop Value (Kvs)	1.23m <sup>3</sup> /h

Kvs value is the metric measure for the flow of a fully opened valve. It is defined as: The volume flow in cubic metres per hour of water at a temperature of between 5° and 40° Celsius with a pressure drop across the valve of 1 bar.

Flow Ratings	
Normal Flow Rate	0.42m <sup>3</sup> /h
Max Flow Rate	1.23m <sup>3</sup> /h

Temperature Ratings	
Max Test Temperature	100°C
Max Operating Temperature	120°C
Temperature Adjustment Range	7-30°C

Disclaimer	
<p>All dimensions are approximate and for roughing in only.            We recommend no work be carried out until the goods arrive.            We can take no responsibility for errors in information supplied.</p>	



# Jaguar Thermostatic Radiator Valve - Corner

