



Rosa Traditional Angled Manual Radiator Valve



| Available Finishes | |
|--------------------|--------|
| Antique Brass | Pewter |
| Satin Nickel | |

| Connection Size | |
|-----------------------------|------|
| To fit Coupler to Radiator | 1/2" |
| Allen Keys are not included | |

| Pressure Ratings | |
|--|--------|
| Max Test Pressure | 12 Bar |
| Max Operating Pressure | 10 Bar |
| Max Differential Pressure | 1 Bar |
| Pressure Drop Value (Kvs) | 1.6 |
| Kvs value is the metric measure for the flow of a fully opened valve. It is defined as: The volume flow in cubic metres per hour of water at a temperature of between 5° and 40° Celsius with a pressure drop across the valve of 1 bar. | |

| Flow Ratings | |
|------------------|----------|
| Normal Flow Rate | 0.25m³/h |
| Max Flow Rate | 0.35m³/h |

| Temperature Ratings | |
|------------------------------|-------|
| Max Test Temperature | 120°C |
| Max Operating Temperature | 110°C |
| Temperature Adjustment Range | N/A |

| Disclaimer | |
|---|--|
| All dimensions are approximate and for roughing in only. | |
| We reserve the right to alter dimensions without notice. | |
| We recommend no work be carried out until the goods arrive. | |
| We can take no responsibility for errors in information supplied. | |

